



## Eckdaten basic data (Sonderausführungen auf Anfrage)

Maximaldrehmoment <i>Maximum torque</i>	$M_{t_{max}}$ $M_{t_{max}}$	<b>11000 Nm</b>	Dauerwechsel Drehmoment <i>Alternating torque</i>	$M_{t_{dw}}$ $M_{t_{dw}}$	<b>5100 Nm</b>
Grenzdrehmoment <i>Limit torque</i>	$M_{t_{grenz}}$ $M_{t_{grenz}}$	<b>17000 Nm</b>	Drehzahl <i>Revolution</i>		<b>1-3000 U/min (rpm)</b>
Betriebstemperatur <i>Operational temperature</i>		<b>-30°C - +120°C</b>			
Rotationsdurchmesser <i>Diameter of rotation</i>		<b>Ø 172 mm (D5)</b>			
Rohrdurchmesser <i>Tube diameter</i>		<b>Ø 120x4 mm (D7)</b>			

<b>GW</b>	<b>500-151</b>	
L1	<b>min.610 mm</b>	
LA	<b>110 mm</b>	

<b>GW</b>	<b>513-151</b>	
L1	<b>470-622 mm</b>	
LA	<b>40-160 mm</b>	

<b>GW</b>	<b>505-151</b>	
L1	<b>min. 440 mm</b>	

<b>GW</b>	<b>528-151</b>		<b>506-151</b>	
L1	<b>400 mm</b>		<b>200 mm</b>	

