



Eckdaten basic data (Sonderausführungen auf Anfrage)

Maximaldrehmoment <i>Maximum torque</i>	$M_{t_{max}}$ $M_{t_{max}}$	5200 Nm	Dauerwechsel Drehmoment <i>Alternating torque</i>	$M_{t_{dw}}$ $M_{t_{dw}}$	2300 Nm
Grenzdrehmoment <i>Limit torque</i>	$M_{t_{grenz}}$ $M_{t_{grenz}}$	7050 Nm	Drehzahl <i>Revolution</i>		1-3000 U/min (rpm)
Betriebstemperatur <i>Operational temperature</i>		-30°C - +120°C			
Rotationsdurchmesser <i>Diameter of rotation</i>		Ø 125 mm (D5)			
Rohrdurchmesser <i>Tube diameter</i>		Ø 80x3.5 mm (D7)			

GW	500-117	
L1	min.530 mm	
LA	110 mm	

GW	513-117	
L1	295-545 mm	
LA	30-110 mm	

GW	505-117	
L1	min. 315 mm	

GW	528-117		506-117	
L1	248 mm (L2=62)		124 mm (L2=62)	



DIN $\varnothing 120/8-10$	DIN $\varnothing 150/8-10$ DIN $\varnothing 150/8-12$	DIN $\varnothing 180/8-14$

SAE $\varnothing 150/4-14.2$ SAE $\varnothing 150/4-12.7$	KV $\varnothing 120/4-11$	KV $\varnothing 150/4-13$